

## Portable AC Unit for Server Rooms - 12,000 BTU (3.5 kW), 230V

MODEL NUMBER: SRXCOOL12K



**Not for sale in California, USA.**

Pumps 12,000 BTU of cold air into server rooms, wiring closets and other IT environments. Ideal for cooling an overheated rack enclosure or an equipment hot-spot inside or outside a rack enclosure.

### Description

The SRXCOOL12K SmartRack 12,000 BTU 230V Portable Server Rack Cooling System pumps 12,000 BTU of cooling power into your IT environment to prevent shutdowns, malfunctions and failures caused by overheating or fluctuating temperatures. Part of the SRCOOL® line, this compact, portable unit is perfect for server rooms and other IT environments with heat-sensitive equipment in areas that facility air conditioning can't reach.

The self-contained SRXCOOL12K is capable of cooling a small room using its louvered vent. A built-in evaporator expels the condensed water through the directional exhaust duct, eliminating the need for a drain tube, drain pan or water collection tank.

You can also use the included flexible tube to aim the cold air precisely where it's needed most, such as an overheated rack enclosure or an equipment hot spot. The SRXCOOL12K Portable Rack Air Conditioner also dehumidifies and filters the air, providing better air quality that can enhance equipment performance with little power consumption.

Designed for quick, simple installation, the SRXCOOL12K rolls on durable built-in casters and plugs into a standard Schuko CEE7 outlet. It's programmed to restart automatically after power failures, and you can set the built-in timer for unattended shutdown and startup.

By installing the optional SRCOOLNETLX remote management accessory (sold separately), you can also monitor temperatures, receive alerts, review logs and control settings from anywhere via SNMP, web browser, SSH or telnet.

### Features

**Compact Cooling** Provides 12,000 BTU/h (3.5 kW) of cooling capacity in a portable chassis Prevents equipment shutdowns, malfunctions and failures caused by overheating and temperature fluctuations Also filters and dehumidifies the air to enhance equipment performance Uses environmentally friendly R410A refrigerant, which complies with worldwide standards

**Convenient Operation** Included 71-inch tube aims cold air where it's needed, such as an overheated rack enclosure or equipment hot spot Built-in evaporator expels condensed water through exhaust tube—no floor drain or water collection tank needed Supports unattended shutdown and startup, including automatic restarts after power failures Intuitive top-panel controls with an informative digital display and diagnostic LEDs System-lock function disables all other buttons to prevent accidental input Optional SRCOOLNETLX remote management accessory (sold separately) allows remote monitoring of temperatures, alerts, logs and control settings from any location via SNMP, web browser, SSH or telnet

**Easy to Install** Rolls into place on built-in casters Plugs into a standard Schuko CEE7 outlet Includes

### Highlights

- Provides 12,000 BTU (3.5 kW) of cooling capacity
- Also filters and dehumidifies air
- Plugs into a standard Schuko CEE7 outlet
- Restarts automatically after power failure
- Can be operated remotely (requires SRCOOLNETLX, sold separately)

### Package Includes

- SRXCOOL12K SmartRack Portable Server Rack Cooling Unit - 12,000 BTU, 230V
- Louvered front vent insert
- Duct adapters
- Cold-air directional delivery tube
- Hot-exhaust removal tube
- Window/drop-ceiling heat-ventilation kit
- Adjustable exhaust panels
- Self-tapping screw
- Warranty information
- Owner's Manual



Powering Business Worldwide



window/drop-ceiling kit for extracting heatNo external condenser, refrigerant piping or professional maintenance required

## Specifications

| OVERVIEW                           |                                                                                    |
|------------------------------------|------------------------------------------------------------------------------------|
| UPC Code                           | 037332145772                                                                       |
| INPUT                              |                                                                                    |
| Nominal Input Voltage(s) Supported | 230V AC                                                                            |
| Nominal Input Voltage Description  | 230V AC 50 Hz                                                                      |
| Input Connection Type              | Schuko CEE7                                                                        |
| Input Plug Features                | Schuko CEE7                                                                        |
| Voltage Compatibility (VAC)        | 230                                                                                |
| Input Frequency                    | 50 HZ                                                                              |
| Input Cord Length (ft.)            | 6                                                                                  |
| Input Cord Length (m)              | 1.83                                                                               |
| COOLING                            |                                                                                    |
| Airflow                            | Evaporator = 329 CFM / Condenser = 311 CFM                                         |
| Cooling Type                       | Active                                                                             |
| Cooling Capacity (BTUs)            | 12000                                                                              |
| Cooling Capacity (kW)              | 3.5                                                                                |
| Refrigerant                        | R410a (Environmentally friendly, Non ozone depleting)                              |
| Refrigerant Amount                 | 22 oz.                                                                             |
| Equivalent Room Size               | 24 sq. m (258.33 sq. ft.)                                                          |
| USER INTERFACE, ALERTS & CONTROLS  |                                                                                    |
| Front Panel LEDs                   | Touch sensitive control panel with multiple LEDs and numerical temperature readout |
| PHYSICAL                           |                                                                                    |
| Color                              | Black                                                                              |
| Material of Construction           | ABS                                                                                |
| Form Factors Supported             | Tower                                                                              |
| Shipping Dimensions (hwd / in.)    | 15.00 x 29.00 x 34.00                                                              |
| Shipping Dimensions (hwd / cm)     | 38.10 x 73.66 x 86.36                                                              |
| Shipping Weight (lbs.)             | 84.00                                                                              |
| Shipping Weight (kg)               | 38.10                                                                              |

|                                     |                          |
|-------------------------------------|--------------------------|
| Unit Dimensions (hwd / in.)         | 30.630 x 11.810 x 19.880 |
| Unit Dimensions (hwd / cm)          | 77.8 x 30 x 50.5         |
| Unit Weight (lbs.)                  | 73.9                     |
| Unit Weight (kg)                    | 33.52                    |
| FEATURES & SPECIFICATIONS           |                          |
| Air Supply Tube Length              | 71 inches                |
| Air Exhaust Tube Length             | 118 inches               |
| Air Exhaust Tube Diameter           | 5.16 inches              |
| Compressor Type                     | Rotary                   |
| Dehumidifier                        | 2.5 liters / hour        |
| Sound Level (Noise)                 | 57dB                     |
| Amp Draw Nominal                    | 7-10A                    |
| STANDARDS & COMPLIANCE              |                          |
| Product Compliance                  | RoHS; CE (Europe)        |
| WARRANTY & SUPPORT                  |                          |
| Product Warranty Period (Worldwide) | 1-year limited warranty  |

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2024 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.