




Part Number : 1068000108
Product Description : FVP Silica/Silica Optical Fiber 200µm, Polyimide, 0.22NA, High -OH (UV-VIS), FVP200240275
Series Number : 106800
Status : Active
Product Category : Optical Fibers
Engineering Number : 2000108



Product Environment Compliance

Compliance

GADSL/IMDS	Not Relevant
China RoHS	
EU ELV	Not Relevant
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2024)4144-DC (27 June 2024)
EU RoHS	Compliant per EU 2015/863

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

Status	Active
Category	Optical Fibers
Series	106800
Description	FVP Silica/Silica Optical Fiber 200µm, Polyimide, 0.22NA, High - OH (UV-VIS), FVP200240275
Application	Industrial, Medical, Research, Scientific, and other
Catalog	www.molex.com/polymicro/catalog
Fiber Series	FVP
More Detailed Tech Information	www.molex.com/polymicro/fv
Product Name	FVP Silica/Silica Optical Fiber
UPC	883906617738
White Paper-Published Articles	www.molex.com/polymicro/whitepapers

Physical

Buffer Diameter	275µm
Buffer Tolerance	± 5µm
Clad Diameter	240µm
Cladding Tolerance	± 4µm
Cladding Type	Doped Silica
Core Diameter	200µm
Core Tolerance	± 4µm
Glass Characteristic	High -OH
Long-Term Bend Radius	4.1cm
Material - Buffer	Polyimide
Material - Glass	Synthetic Fused Silica
Net Weight	0.120/g
Numerical Aperture	0.22
Packaging Type	Spool
Proof Tested @ Minimum 100kpsi	100% for Strength
Short-Term Bend Radius	1.2cm
Temperature Range - Operating	-65° to +300°C
Wavelength Range	180nm - 1150nm (High -OH)

Wire/Cable Type	Silica Optical Fiber
-----------------	----------------------

Use with Part(s)

Description	Part Number
Use With	Ferrules, Sleeves, SMA Connectors, and Custom Connectors