



**Part Number :** [2076025008](#)

**Product Description :** Grounding Jumper without Insulation, Flat-to-Flat, 48x24/36 Braid Type, 607.00mm Length

**Series Number :** 207602

**Status :** Active

**Product Category :** Busbars



---

## Documents & Resources

### Drawings

[2076025008\\_sd.pdf](#)

### Specifications

[2076025000-PS-000.pdf](#)

---

## Product Environment Compliance

### Compliance

|                    |              |
|--------------------|--------------|
| China RoHS         | Not Reviewed |
| EU ELV             | Not Reviewed |
| Low-Halogen Status | Not Reviewed |
| REACH SVHC         | Not Reviewed |
| EU RoHS            | Not Reviewed |

### Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

### Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

### EU RoHS Certificate of Compliance

---

Part Details

General

|              |                                                                                           |
|--------------|-------------------------------------------------------------------------------------------|
| Status       | Active                                                                                    |
| Category     | Busbars                                                                                   |
| Series       | 207602                                                                                    |
| Description  | Grounding Jumper without Insulation, Flat-to-Flat, 48x24/36 Braid Type, 607.00mm Length   |
| Keyword      | grounding jumpers, grounding strap, grounding straps, ground strap, ground straps, busbar |
| Product Name | Grounding Jumper                                                                          |
| UPC          | 191128899017                                                                              |

Electrical

|                               |        |
|-------------------------------|--------|
| Current - Maximum per Contact | 105.0A |
|-------------------------------|--------|

Physical

|                                |              |
|--------------------------------|--------------|
| Approximate AWG Equivalent     | 6            |
| Approximate Circular Mils      | 28800        |
| Braid Type                     | 48x24/36     |
| Insulation                     | None         |
| Length                         | 607.00mm     |
| Material - Metal               | Copper       |
| Material - Plating Mating      | Tin          |
| Material - Plating Termination | Tin          |
| Orientation                    | Flat-to-Flat |
| Packaging Type                 | Carton       |